


Horizontallathes













**Horizontal**lathes Accessories **Devices** 

# **Machining Accessories**

## Main Spindle bore - options

Spindle bore diameter	mm	162	230	322	360	412	525	535
Main spindle nose	DIN55026	15	15	20	20	28	28	28
Diameter of front spindle bearing	mm	220	280	394	432	480	650	650
Spindle Speed	Min <sup>-1</sup>	900	700	500	500	400	400	400



Chucks

Steady rests


Second saddle


## **Measuring probes**

-Probes for tool measurement. -Probes for parts measurement.

## **Guarding options**


- Full enclosure.













## **Machining devices**

- Milling device -Milling device on turret.
- -Milling device on turret with Y-axis.
- -Milling column.
  -Milling column with Y- & B-axis

## Boring device

- -Boring bar on turret.
- -Boring bar device instead of the turret.

- Grinding device
  -Grinding device on turret.
  -Grinding device instead of turret.
- -Grinding cycles.
- -External & internal grinding solutions.

### Polishing device

**Burnishing device** 

Quick change system













Iron & Steel












Oil & Gas



Railway







Wind Energy




Pulp and Paper








Shipyard



Cranes







**GORATU** Máquinas Herramienta, S.A.

Lerún, 1 - 20870 Elgoibar Gipuzkoa (Spain) Tel. +34 943 748 060 Fax +34 943 744 093 sales@goratu.com

www.goratu.com



Goratu Máquinas Herramienta, S.A. accepts no responsibility for any possible printing or typing errors, and reserves the right to include any modification to the characteristics of the products with no prior notice. The pictures showed do not necessarily fit with the standard machine's configuration.