



Benchtop portable model available



FEATURES

- Standard steel tube capacity 42 x 3 mm
- Pipe capacity 1" Sch. 40
- Square tube capacity 35 x 35 x 3 mm
- Bending radii 10 ÷ 260 mm
- Bend to CLR as small as 2D
- Touch screen control offers easy access to auto and manual operating modes, programming, system diagnostics and multiple language capability
- Patented quick-change tooling system with multiple radii available
- Single Bending Speed
- Benchtop portable model available

TECHNICAL DATA

Flection Modulus	4.1 cm ³
Minimum Outside Diameter	10 mm - 1/8" Gas
Maximum Shaft Speed	2 - 4 rpm
Maximum Center Line Radius (CLR)	260 mm
Minimum Center Line Radius (CLR)	10 mm
Power	1.1 kW
Voltage Requirement	110 - 220 V 220 - 400 V 3PH / 50 - 60 Hz
Weight	80 Kg / 50 Kg
Dimensions (L x W x H)	410 x 1000 x 570 mm - 360 x 500 x 460 mm

	MAXIMUM CAPACITY	MB42 / MB42P
	Gas tubes	1"1/4 Gas x 3.5
	Standard Steel tubes	42 x 3 mm
	Furniture tubes	48 x 1.5 mm
	Hydraulic Steel ST35	42 x 4 mm
	Stainless Steel AISI 304 - 316	42 x 3 mm
	Stainless Steel AISI 308 (food industry)	42 x 2.5 mm
	Soft Brass	50 x 3 mm
	Hard Copper & Aluminium	54 x 2 mm
	Soft Copper	60 x 2 mm
	Conduit tubes	60 x 2 mm
	Mepla, Geberit and similar tubes	50 x 4 mm
	Mild Steel (EN: S275JO)	30 mm
	Mild Steel (EN: S275JO)	7 x 42 mm
	Mild Steel (EN: S275JO)	18 x 35 x 2 mm
	Mild Steel (EN: S275JO)	35 x 35 x 3 mm
	Mild Steel (EN: S275JO)	25 x 25 mm
	Mild Steel (EN: S275JO)	35 x 35 x 5 mm
	Mild Steel (EN: S275JO)	28 x 15 x 5 mm

MAXIMUM CAPACITIES AND MINIMUM RADII ARE INDICATIVE AND NOT BINDING